



DEPOSITA[®]
An ALLIED UNIVERSAL[™] Company

PROTECTOR
3 000 RANGE



RECEIPT

NEVER COMPROMISE ON SECURITY FOR SPACE

Many businesses don't have the space to spare for the size of smart-safe they need. You could opt for a smaller safe with more frequent cash-in-transit collections. But this is often costly, impractical and disruptive. We designed the Protector 3 000 range to be high-speed counting, high-capacity, smart-safes that take up a fraction of the space. Make your business more efficient and safer for employees and customers. Plus, reduce insurance, security, cash-in-transit costs and more. That's time and money you and your staff can devote to your customers and your business.

Reduce the time it takes counting money so you and your staff can focus on your customers. Our industry-leading cash-handling devices run on bespoke software to automate and streamline your cash management and payment reconciliation saving you time and money.

CHANGE HOW YOU SEE YOUR BUSINESS'S
POTENTIAL WITH THE COMPACT, HIGH-SPEED,
HIGH-CAPACITY INTELLIGENT SAFE.

PROTECTOR 3 000 RANGE

- High-speed note validation of up to 720 banknotes per minute
- Traceable cash containers
- Connector: real-time device information, transaction tracking, custom reports and remote monitoring
- Back-up battery for transaction completion
- 24-hour on-site visibility and tamper notification
- Contactless card, biometric fingerprint or on-device touchscreen access

CASH-HANDLING SOLUTIONS THAT INCREASE
EFFICIENCY HEIGHTEN SECURITY AND
STREAMLINE CASH FLOWS.





MAKE CASH MANAGEMENT MORE INTELLIGENT WITH CONNECTOR

Our comprehensive family of software tools create a powerful, flexible financial transaction platform to suit your business. Improve efficiency and effectiveness of cash management across payment channels and operating systems. Secure, consolidate and make your data easily accessible to decision-makers.

Contact us: deposita.salesadmin@za.g4s.com or +27 (0)11 729 3300



PROTECTOR 3 000 d-s1

DIMENSIONS AND WEIGHT

HEIGHT (validator closed / open)	799mm / 873mm
WIDTH	464mm
DEPTH	600mm
WEIGHT	150kg

CAPACITY

1 x 3 000 note stackerless bag
3 000 ATM note quality smart-safe capacity

DEPOSIT ACCEPTANCE

1 x note validator that validates notes irrespective of their orientation
720 notes per minute
Infrared and UV note validation
Fraud and dye-stain detection and rejection
400 notes stacked per hopper
200 notes escrow
Remote currency updates

SECURITY

Seismic notification if the device is tampered with
Electronic smart lock with two-factor authentication

USER INTERFACE

9" Touch screen

ACCESSIBILITY

Contactless technology
Touch screen on-device user management



CIT ACCESS

Keyless controlled cash-in-transit entry via device-specific issued and controlled contactless technology accompanied by a one-time pin authentication

Front clearance for your cash-in-transit service provider

WEB INTERFACE

CONNECTOR REPORT - real-time device information, transaction tracking, custom reports and remote monitoring

COMMUNICATION

Mobile (GSM) / Local area network (LAN)

PRINTER

203dpi thermal printer (58mm)

ADDITIONAL OPTIONS

Multi-account banking
Customer point-of-sale integration
Unique, on-device reference capture
Biometric fingerprint verification
Uninterruptible power supply

POWER CONSUMPTION

AC 110-120V ~ /220-240V ~ 50-60HZ
Idle: 65W
Maximum working: 130W

WORKING ENVIRONMENT

Operating temperature 32°F (0°C) to 104°F (40°C)
Relative humidity: 20% to 95% non-condensing

CERTIFICATION

ISO 9001
ISO 27001
UL 291

WARRANTY

Full maintenance plan over the contract period



PROTECTOR 3 000 d-s2

DIMENSIONS AND WEIGHT

	Under-Counter	Through-The-Wall
HEIGHT	890mm	1 000mm
WIDTH	516mm	526mm
DEPTH	509mm/527mm	703mm/795mm
WEIGHT	116kg	123kg

CAPACITY

1 x 3 000 note stackerless bag
3 000 ATM note quality smart-safe capacity

DEPOSIT ACCEPTANCE

2 x note validators validate notes irrespective of their orientation
40 notes per minute per validator
Infrared note validation
Fraud and dye-stain detection and rejection
40 notes stacked per hopper
Remote currency updates

MODULARITY

Optional 25kg coin sidecar

SECURITY

Seismic notification if the device is tampered with

USER INTERFACE

7" Touch screen

ACCESSIBILITY

Mifare card
Touch screen on-device user management



<p>CIT ACCESS</p>	<p>Keyless controlled cash-in-transit entry via device-specific issued and controlled access cards</p> <p>Front or back clearance for your cash-in-transit service provider</p>
<p>WEB INTERFACE</p>	<p>CONNECTOR REPORT - real-time device information, transaction tracking, custom reports and remote monitoring</p>
<p>COMMUNICATION</p>	<p>Mobile (GSM) / Local area network (LAN)</p>
<p>PRINTER</p>	<p>200dpi panel printer (58mm)</p>
<p>ADDITIONAL OPTIONS</p>	<p>Multi-account banking</p> <p>Customer point-of-sale integration</p> <p>Biometric fingerprint verification</p> <p>Plinth (height and storage)</p> <p>Uninterruptible power supply</p> <p>Unique, on-device reference capture</p>
<p>POWER CONSUMPTION</p>	<p>AC 110-120V ~ /220-240V ~ 50-60HZ</p> <p>Idle: 65W</p> <p>Maximum working: 130W</p> <p>Battery back-up for transaction completion</p>
<p>WORKING ENVIRONMENT</p>	<p>Operating temperature 32°F (0°C) to 104°F (40°C)</p> <p>Relative humidity: 20% to 95% non-condensing</p>
<p>CERTIFICATION</p>	<p>ISO 9001</p> <p>ISO 27001</p> <p>International Electrotechnical Commission (IEC) 60950-1</p>
<p>WARRANTY</p>	<p>Full maintenance plan over the contract period</p>



PROTECTOR 3 000 d-s3

DIMENSIONS AND WEIGHT

HEIGHT	1 040mm
WIDTH	576mm
DEPTH	622mm
WEIGHT	420kg

CAPACITY

1 x 3 000 note stackerless bag
3 000 ATM note quality smart-safe capacity

DEPOSIT ACCEPTANCE

2 x note validators validate notes irrespective of their orientation
40 notes per minute per validator
Infrared note validation
Fraud and dye-stain detection and rejection
40 notes stacked per hopper
Remote currency updates

MODULARITY

Optional 25kg coin sidecar

SECURITY

Seismic notification if the device is tampered with
Built to Category 3 (CAT3) specifications

USER INTERFACE

7" Touch screen

ACCESSIBILITY

Mifare card
Touch screen on-device user management



CIT ACCESS

Keyless controlled cash-in-transit entry via device specific issued and controlled access cards

Front or back clearance for your cash-in-transit service provider

WEB INTERFACE

CONNECTOR REPORT - real-time device information, transaction tracking, custom reports and remote monitoring

COMMUNICATION

Mobile (GSM) / Local area network (LAN)

PRINTER

200dpi panel printer (58mm)

ADDITIONAL OPTIONS

Multi-account banking
Customer point-of-sale integration
Biometric fingerprint verification
Uninterruptible power supply
Unique, on-device reference capture

POWER CONSUMPTION

AC 110-120V ~ /220-240V ~ 50-60HZ
Idle: 65W
Maximum working: 130W
Battery back-up for transaction completion

WORKING ENVIRONMENT

Operating temperature 32°F (0°C) to 104°F (40°C)
Relative humidity: 20% to 95% non-condensing

CERTIFICATION

ISO 9001
ISO 27001
International Electrotechnical Commission (IEC) 60950-1

WARRANTY

Full maintenance plan over the contract period

DO MORE WITH WHAT'S YOURS™

ISO 27001 & ISO 9001 Accreditation



Customer Service Centre: 0861 000 965 Tel: +27 (0)11 729 3300 deposita.salesadmin@za.g4s.com
1 Slate Avenue. N1 Business Park. Old Pretoria Road. Midrand. Johannesburg. South Africa.

www.deposita.co.za