



DEPOSITA[®]
An ALLIED UNIVERSAL[™] Company

PROTECTOR
4 000 RANGE



SA7659318 A

10

SUID-AFRIKAANSE RESERWEBANK

Modibane



LIBHANGESILULU LENINGIZIMU AFRIKA

10

SA7659318 A

TEN RAND

Modibane - Casselton 1978 - 2018

RELENTLESS PERFORMANCE, UNRELENTING SECURITY

Running a business with high volumes of cash, you need extraordinary security and efficiency. Our industry-leading, high-speed smart-safes offer an all-in-one solution to secure and streamline your cash flow. Allowing you to improve your customers' experience and staff performance while saving time and money. Plus, reduce insurance, security, cash-in-transit costs and more. That's time and money you and your staff can devote to your customers and your business.

WE DO MORE THAN PROTECT MONEY.
WE SAVE YOU AND YOUR ENTERPRISE
FROM THE COSTS OF HANDLING CASH.

PROTECTOR 4 000 RANGE

- Biometric, touchscreen or card user access
- 24-hour on-site visibility and tamper notification
- Traceable cash containers
- Back-up battery for transaction completion
- Improve cash-in-transit efficiency
- CONNECTOR REPORT: Track and view transactions and create custom reports via the web
- International standard of quality and performance

WE DEVELOP SUPERIOR, INNOVATIVE PRODUCTS
THAT OFFER MORE FUNCTIONALITY, MORE
EFFICIENCY AND MORE SECURITY.









MAKE CASH MANAGEMENT MORE INTELLIGENT WITH CONNECTOR

Our comprehensive family of software tools create a powerful, flexible financial transaction platform to suit your business. Improve efficiency and effectiveness of cash management across payment channels and operating systems. Secure, consolidate and make your data easily accessible to decision-makers.

Contact us: deposita.salesadmin@za.g4s.com or +27 (0)11 729 3300



PROTECTOR 4000 d-s1

DIMENSIONS AND WEIGHT

HEIGHT (validator closed / open)	908mm / 1 311mm
WIDTH	725mm
DEPTH	667mm
WEIGHT	189kg

CAPACITY

1 x 4 000 note stackerless bag
4 000 ATM note quality smart-safe capacity

DEPOSIT ACCEPTANCE

1 x note validator that validates notes irrespective of their orientation
600 notes per minute
Infrared and UV note validation
Fraud and dye-stain detection and rejection
200 notes stacked per hopper
100 notes escrow
Remote currency updates

MODULARITY

Optional 25kg coin sidecar

SECURITY

Seismic notification if the device is tampered with

USER INTERFACE

10" Touch screen

ACCESSIBILITY

Mifare card
Touch screen on-device user management



CIT ACCESS

Keyless controlled cash-in-transit entry via device-specific issued and controlled access cards
Front or back clearance for your cash-in-transit service provider

WEB INTERFACE

CONNECTOR REPORT – real-time device information, transaction tracking, custom reports and remote monitoring

COMMUNICATION

Mobile (GSM) / Local area network (LAN)

PRINTER

384dpi thermal printer (48mm)

ADDITIONAL OPTIONS

Multi-account banking
Biometric fingerprint verification
Customer point-of-sale integration
Unique reference capture
Failsafe for unverified deposits
Built to Category 3 (CAT3) specifications
Through-the-wall (TTW)
Uninterruptible power supply

POWER CONSUMPTION

AC 110-120V ~ /220-240V ~ 50-60HZ
Idle: 65W
Maximum working: 130W

WORKING ENVIRONMENT

Operating temperature 32°F (0°C) to 104°F (40°C)
Relative humidity: 20% to 95% non-condensing

CERTIFICATION

ISO 9001
ISO 27001
International Electrotechnical Commission (IEC) 60950-1

WARRANTY

Full maintenance plan over the contract period



PROTECTOR 4 000 d-s2

DIMENSIONS AND WEIGHT

HEIGHT (validator closed / open)	908mm / 1 412mm
WIDTH	725mm
DEPTH	667mm
WEIGHT	189kg

CAPACITY

1 x 4 000 note stackerless bag
4 000 ATM note quality smart-safe capacity

DEPOSIT ACCEPTANCE

1 x note validator that validates notes irrespective of their orientation
360 notes per minute
Infrared and UV note validation
Fraud and dye-stain detection and rejection
200 notes stacked per hopper
Remote currency updates

MODULARITY

Optional 25kg coin sidecar

SECURITY

Seismic notification if the device is tampered with

USER INTERFACE

10" Touch screen

ACCESSIBILITY

Mifare card
Touch screen on-device user management



CIT ACCESS	Keyless controlled cash-in-transit entry via device-specific issued and controlled access cards Front or back clearance for your cash-in-transit service provider
WEB INTERFACE	CONNECTOR REPORT – real-time device information, transaction tracking, custom reports and remote monitoring.
COMMUNICATION	Mobile (GSM) / Local area network (LAN)
PRINTER	384dpi thermal printer (48mm)
ADDITIONAL OPTIONS	Multi-account banking Biometric fingerprint verification Customer point-of-sale integration Unique, on-device, reference capture Built to Category 3 (CAT3) specifications Through-the-wall (TTW) Uninterruptible power supply
POWER CONSUMPTION	AC 110-120V ~ /220-240V ~ 50-60HZ Idle: 65W Maximum working: 130W
WORKING ENVIRONMENT	Operating temperature 32°F (0°C) to 104°F (40°C) Relative humidity: 20% to 95% non-condensing
CERTIFICATION	ISO 9001 ISO 27001 International Electrotechnical Commission (IEC) 60950-1
WARRANTY	Full maintenance plan over the contract period

DO MORE WITH WHAT'S YOURS™

ISO 27001 & ISO 9001 Accreditation



Customer Service Centre: 0861 000 965 Tel: +27 (0)11 729 3300 deposita.salesadmin@za.g4s.com
1 Slate Avenue. N1 Business Park. Old Pretoria Road. Midrand. Johannesburg. South Africa.

www.deposita.co.za